

DROP DECK HAUL TRAILERS

10+27+5 with 25K Dexter Axles

14" 26 lb. I-Beam Main Frame Pierced
3" Channel Crossmembers on 12" Centers Through Beam
Kickers every 24" from Main Frame to Crossmembers
6" Channel Sides with 3/8" X 2" Rub Rail and Stakepockets
10' Upper Deck (Available in Different Lengths)
27' Main Floor, 5' Dove Tail (with 6' Dove Option)
5' Dozer Ramps with Spring Assist (with 6' Option)
Air Brakes and Hutch Suspension
Air Brake Axles will be Equipped with ABS on one Axle
Torque Tube or Sway Control
215 X 75R-17.5 16 Ply Tires
LED Lights, DOT Tape
Underside Tool Box, D-Rings, and Slide Cargo Winches
Spare Tire & Storage, 2-Speed Jacks
3/4" Plate Mounted Under Main Beams on Upper Deck
with King Pin Welded Flush Inside
Saw Mill Cut Oak Floor
Other Lengths Available



GOOSENECK DUMP TRAILER

12" 19 lb. I-Beam A Frame and Neck
Crossmembers on 12" Centers
Standards on 16" Centers
2) 10K Dexter Axles (with 12K and 15K Option)
2) 12K Bulldog Dropleg Jacks (2-Speed Option)
Electric Brakes (Hydraulic or Air Option)
Colt Hoist with Corded Outside Remote
45" X 8' X 16' Bed with Barn Door or
Spreader Door (Optional)
12 Gauge Sides and Bottom
2 Band Support on Sides
ST235 X 80R-16 Tires with Rating at 3420 lbs. each
DOT Tape
8' Ramps with Storage (Option)
*Dump Trailers are Available in Different Sizes
and Capacities



DEALER INQUIRES ONLY



EXPRESS TRAILERS



QWS Express Trailers is a family owned and operated business with over 28 years of service in the welding and fabrication industry. We take pride in craftsmanship. Our employees are certified welding and fabrication professionals. All of our trailers are built with stability, quality craftsmanship and pride. Each trailer is custom built from high end materials to your specifications and come with a one year warranty. They are cleaned, undercoated with primer, primed and painted with two coats of acrylic paint (Valspar Matching Available) and delivered to their final destination. We build each trailer as if we were going to use it ourselves.

CUSTOM BUILT AND PREPPED FOR DELIVERY



Thank you for your inquiry and choosing
QWS EXPRESS TRAILERS, INC.

SINGLE AXLE UTILITY TRAILERS

5' x 8', 10', 12', or 14' Available with Gate, Tilt Style, or No Gate.

Crossmembers, Frames, Standards and Toprail: 2" X 3" X 3/16" Angle

Tongue: 3" X 3" X 3/16" Angle with

2" X 2" X 3/16" Angle Tongue Brace

Ramp Gate: 2" X 3" X 3/16" Angle with Expanded Metal

Floor: Treated Yellow Pine

Single Axle: 3500 lb. Axle

Fenders: Treadplate with Precut Back

Coupler: Atwood A-Frame

Jack: Top Wind with Jack Brace

Tires: ST205 X 75D-15 6 Ply (New)



SINGLE AXLE UTILITY TRAILERS

77' x 10', 12', or 14'

These Trailers are Great for Mowers with Wide Decks

Frame: 4" Channel and Wrap Tongue

Crossmembers: 2" X 2" X 3/16" on 16" Centers

Standards and Toprail: 2" X 3" X 3/16" Angle

Tongue: 4" Channel Wrap

Floor: Treated Yellow Pine (Flush with sides)

Single Axle: 3500 lb. Axle

Fenders: Threadplate with Precut Backs

Coupler: Atwood A-Frame

Jack: Top Wind 2000 lb. (Flip Jack Option)

Tires: ST205 X 75D-15 6 Ply



7000 LB. GVW UTILITY TRAILERS

Crossmembers, Frame, Standards and Toprail: 2" X 3" X 3/16" Angle

Tongue: 4" Channel Wrapped

Floor: Treated Yellow Pine

Axles: (2) 3500 lb. Axles

Coupler: Atwood A-Frame Couplers

Jack: Top Wind 2000 lb. (Flip Jack Option)

Tires: ST205 X 75D-15 6 Ply



83" X 16', OR 18" UTILITY TRAILER

Frame: 4" Channel

Tongue: 4" Channel Wrapped

Crossmembers, Standards and Toprail: 2" X 2" X 3/16" Angle on 16" Centers

Floor: Treated Yellow Pine

Axles: (2) 3500 lb. or 5200 lb. Dexter Axles

Fenders: Treadplate

Coupler: Bulldog Coupler

Jack: Top Wind

Tires: 3500 lb. ST205 X 75D-15 6 Ply on 7,000 lb. GVW

5200 lb. ST225 X 75D-15 8 ply on 10,400 lb. GVW (with 16" Tire Option)



All Utility Trailers include: Lights, License Plate Bracket and Safety Chain

SINGLE AND TANDEM AXLE UTILITY OPTIONS

- ❖ Pipe Top
- ❖ Spare Tire and Holder
- ❖ Larger Axles
- ❖ Drop Leg Jack
- ❖ Ramp Gates
- ❖ Bulldog Coupler
- ❖ A-Frame Tool Box
- ❖ Flip Jack
- ❖ Brakes on One or Both Axles
- ❖ 4' Ramps and Storage

40' TANDEM DUAL SPREAD AXLE STRAIGHT DECK HOT SHOT GOOSENECK

(2) 10K Dexter Axles Spread for Better Weight Distribution

12" 19 lb. Main Frame and Neck

3" Channel Crossmembers on 16" Centers

6" Channel Sides

Knee Braces every 32"

Sway Control

Bridge Under Beam

Stakepockets on 16" Centers

3/8" X 2" Flat Rub Rail

Sliding Adjustable Cargo Winches with 30' Straps

Underside Tool Box Between Axles on Each Side

Locking Chain Rack

235 X 85R-16 10 Ply Tires

Treated Floor

2-Speed Jacks

20K Adjustable Coupler

3" Channel Ramps 8' Long with Slide in Storage at Rear

LED Lights



8' Ramp w/ Slide in Storage

OPTIONS AVAILABLE ON GOOSENECK TRAILERS



2 - Speed Jack Option



Locking Chain Rack



Spread Axle w/ Undermount Tool Box on Each Side



3rd Ramp Option



Diamond Plate on Ramps



Plated Ramps and Pop-up



D-Ring Tie Downs



Chrome Simulator



Slide Cargo Winches

Other Options Available but not Pictures are:

14 & 16 Ply Tires, Larger Axles, Vacuum over Hydraulic, Electric over Hydraulic, and Air Brakes

LOW PROFILE PIERCED FRAME GOOSENECK

Low Profile Gooseneck Trailers for Better Loading and less height. By piercing the beam it allows you to run the cross members through the beam 1 1/2" below the top of the beam. This allows the floor to be flush with the top of the beam, lowering the height of the trailer floor 4 1/2". Also we put 225 X 75R-16 tires on the trailer lowering it two more inches. These trailers are popular with equipment haulers. Low Profile trailers have the same specs as the tandem dual gooseneck trailers, except treadplate over the wheels to allow more tire clearance.



Flush Floors on Pierced Beam Trailers



22 + 5 Tandem



22 + 5 Tandem Dual



22 + 5 Tandem Dual



22 + 6 Tandem Dual



40 + 5 Tandem Dual

PIECED FRAME PINTLE HITCH EQUIPMENT TRAILERS

20+5 w/10K Dexter Axles & Electric Brakes/Pierced Beam
22+5 w/10K Dexter Axles & Electric Brakes/ Pierced Beam



16 + 2 AND 18 + 2 CAR HAULERS

Available with 7K GVW or 10,400 GVW, with Wood or Steel Floors, and 1 Brake Axle or 2 Brake Axles

Frame and Tongue: 4" Channel Frame with Wrap Tongue
Crossmembers: 3" Channel on 16" Centers on Wood Floors
Or 12" Centers on Steel Floors
Floor: Treated Yellow Pine Floor or Treadplate
Fenders: Treadplate
Coupler: 2" or 2 5/16" Bulldog Coupler
Tires: 7K Car Haulers have new ST205 X 75D-15 6 Ply Tires
10,400K Car Haulers have new ST225 X 75D-15 8 Ply Tires
Center Tongue Brace
Swivel Jack Set Back on Center Tongue Brace
Breakaway Kit
Safety Chains
Bump Rail on Front
Rubber Mounted Recessed Lights (LED Option)
Stakepockets and 4 D-Ring Tie Downs
5' Treadplate Slide in Ramps from Rear
Ramp Storage with Access Doors in Bumper
D.O.T. Tape
Angle Front
A-Frame Tool Box (Option)



10,400 LB. 12 AND 14K GVW EQUIPMENT TRAILERS

With 5' Stand Up or Slide in Ramps.
Also in 16+2, 18+2, or 18' and 20' Straight Decks

Frame: 5" Channel Frame and Wrap Tongue on 10,400K
6" Channel Frame and Wrap Tongue (12 & 14K)
Crossmember: 3" Channel Crossmembers on 16" Centers
Coupler: 2 5/16" Bulldog Coupler on 12K Trailer
14K Adjustable Hitch on 14K Trailers
Axles: 5,200, 6K or 7K Dexter Axles with Electric Brakes
Tires: 235 X 85R-16 10 Ply Radial Tires
Fenders: Treadplate
8K Bulldog Drop Leg Jack
5' 3" Channel Stand Up or Slide In Ramps
Rubber Mounted Recessed Lights
Safety Chains
Stake Pockets
D.O.T. Tape



10,400 LB. 12 AND 14K GVW EQUIPMENT TRAILER OPTIONS

- ❖ Convert to Pipe Top
- ❖ Spare Tires with Holder
- ❖ Add a Neck
- ❖ Steel Floors
- ❖ A-Frame Tool Boxes
- ❖ LED Lights

GOOSENECK TRAILERS

18 + 2 OR 22 + 2 LOWBOY UTILITY

GOOSENECK

- 8" I-Beam Neck
- 6" Channel Sides w/5" Channel Reinforcement from Tires Forward
- 3" Channel on 16" Centers on Wood Floors or 12" Centers on Steel Floor
- (2) 7K Dexter Axles with Electric Brakes
- 20K 2 5/16" Bulldog Adjustable Coupler
- Treadplate Fenders
- Rubber Mounted Sealed Beam Lights (LED Option)
- 2' Treadplate Dove
- 5' 3" Channel Standup Ramps (Slide In with Storage Option)
- Treated Floors
- Safety Chains
- 12K Drop Leg Jack (with 2nd Jack Option)
- Tires 7.50 X 16 10 Ply Tires (235 X 85R-16 10 Ply Radials Option)
- Spare Tire (Option)



20 + 5 TANDEM GOOSENECK 14K GVW

WOOD FLOORS AND WOOD DOVE

- 10" 12 lb I-Beam Frame and Neck
- 5" Channel Sides
- 3" Channel Crossmembers on 24" Centers
- (2) 7K Dexter Axles with Electric Brakes
- 20K 2 5/16" Bulldog Adjustable Coupler
- (1) 12K Bulldog Drop Leg Jack (with 2nd Jack Option)
- 5' Wood Dove
- 5' 3" Channel Standup Ramps with Stationary Blocks
- Treated Floors
- Knee Braces, Stakepockets
- 3/8" X 2" Flat Rub Rail
- 7.50 X 16 10 Ply Tires (Spare Tire Option)



20 + 5, 22 + 5, OR 25 + 5

14K TANDEM GOOSENECK

- 14# 12" I-Beam Frame and Neck
- 3" Channel Crossmembers on 24" Center (with 16" Center Option)
- 5" Channel Sides, Knee Braces every 24"
- 7K Dexter Axles w/Slipper Springs & Electric Brakes
- 20K 2 5/16" Bulldog Adjustable Coupler
- (2) 12K Bulldog Drop Leg Jacks
- Breakaway Kit
- (2) Spring Assist Ramps
- Self Cleaning Dove
- Rubber Mounted Recessed Lights (LED Option)
- Side Turn Signals
- Treated Yellow Pine Floor
- Chain Rack, Safety chains
- D.O.T. Tape
- Stakepockets
- 3/8" x 2" Rub Rail
- Tires 235 X 85R-16 Radial Tires with Spare



20 + 5 & 22 + 5 TANDEM DUAL

25 + 5 & 27 + 5 TANDEM DUAL W/BRIDGE

- 12" 19# I-Beam Neck and Frame
- 6" Channel Iron Sides
- 3" Channel Crossmembers on 16" Centers
- (2) 10K Dexter Axles with Electric Brakes
- 20K 2 5/16" Bulldog Adjustable Coupler
- (2) 12K Bulldog Dropleg Jacks
- 5' Dove Tail (Self Cleaning)
- (2) Spring Assisted Ramps
- Knee Braces every 32"
- Treated Yellow Pine Floor
- Bridge Under Frame (All Trailers 30' and above have Bridge under Frame)
- Anti-Sway Control on Tandem Duals
- Break Away Box & Safety Chain
- Rubber Mounted Recessed Lights (LED Option)
- D.O.T. Tape
- Stakepockets
- 3/8" X 2" Rub Rail
- 235 X 85R-16 10 Ply Radial Tires with Spare
- Mud Flaps
- Side Marker Turn Signals



20 + 5 Tandem Dual



27 + 5 Tandem Dual


STANDARD FEATURES ON GOOSENECK TRAILERS



Step on Side for Easy, On/Off Access & Rubber Mounted Recessed Lights



10-Ply Radial Tires



Treated Floors



Coupler Safety Chains



Bridging on Tandem Dual with Spare Tire 30' and Above (Option on Shorter Trailers)



Spring Assisted Ramps